



NOTE: INLET & OUTLET CONNECTIONS INDICATED (STAMPED) ON TRAP
 PRESSURES TO 600 PSIG @ 150°F ONLY
 DISCHARGE IN S.C.F.M.

INLET-OUTLET CONNECTION
 1/2 & 3/4 NPT

NPT	TRAP NO.	OPERATING PRESSURE (DIFFERENTIAL PRESSURE)										
		15	30	50	75	100	125	150	200	250	300	400
1/2	SVV-2	7.3	11	15.5	21	17	20.6	24.0	16.2	20	24	28
3/4	SVV-3	7.3	11	15.5	21	17	20.6	24.0	16.2	20	24	28
	ORIFICE DIA.	7/32	7/32	5/32	5/32	7/64	7/64	3/32	5/64	5/64	5/64	5/64

DESIGN PRESSURE 500PSIG TEMP. UP TO 500°F NET WEIGHT: 5 LBS.

Materials
 DRAWN: JWK SCALE: NONE
 CHECKED: DATE: 3-14-83

THE **CLARK-RELIANCE** CORP.
 CLEVELAND, OHIO, U.S.A.

VENT TRAP STAINLESS STEEL
 SVV 1/2 OR 3/4

DRAWING NO. T-3363-A REV. 3