



**COVER GASKET**  
Non-asbestos

**VALVE ASSEMBLY**  
 Bracket 302 SST  
 Seat Gasket - Monel  
 Seat 416 SST  
 Lever 302 SST  
 Disc 416 SST  
 Disc Lock 302 SST

**COVER**  
304 SST

**COVER BOLT & NUT**  
Quantity 10  
Steel Gr. 5 0-500 PSIG

**FLOAT**  
304 SST

**BODY**  
304 SST

**INLET:** 1/2 NPT-.703 DIA. THRU  
3/4 NPT-.812 DIA. THRU

**NOTE:** INLET & OUTLET CONNECTIONS INDICATED (STAMPED) ON TRAP  
 PRESSURES TO 600 PSIG @ 150°F ONLY  
 DISCHARGE IN S.C.F.M.

**INLET-OUTLET CONNECTION**  
1/2 & 3/4 NPT

NPT	TRAP NO.	OPERATING PRESSURE (DIFFERENTIAL PRESSURE)										
		15	30	50	75	100	125	150	200	250	300	400
1/2	SVV-2	7.3	11	15.5	21	17	20.6	24.0	16.2	20	24	28
3/4	SVV-3	7.3	11	15.5	21	17	20.6	24.0	16.2	20	24	28
	ORIFICE DIA.	7/32	7/32	5/32	5/32	7/64	7/64	3/32	5/64	5/64	5/64	5/64
		DESIGN PRESSURE 500PSIG			TEMP. UP TO 500°F			NET WEIGHT: 5 LBS.				

**Materials**

**DRAWN:** JWK      **SCALE:** NONE  
**CHECKED:**      **DATE:** 3-14-83

THE **CLARK-RELIANCE** CORP.  
 CLEVELAND, OHIO, U.S.A.

**VENT TRAP STAINLESS STEEL**  
 SVV      1/2 OR 3/4

**DRAWING NO.**  
T-3363-A

**REV.**  
3