

16433 Foltz Pkwy Strongsville, Ohio 44149 Telephone: (440) 572-1500 Fax: (440) 572-0900  
www.clark-reliance.com



**S366 – 0050 – B – 1**

Element Type/Dimensions

Center Core Material

Absolute Micron Rating

Gasket Material

**Filtration Efficiency Rating: ISO 16889**

<u>Element Part Number</u>	<u>Average Filtration Ratio</u>
S366-0010-B-1	Beta <sub>(x)</sub> 75 @ 1.0 uM
S366-0030-B-1	Beta <sub>(x)</sub> 75 @ 3.0 uM
S366-0050-B-1	Beta <sub>(x)</sub> 75 @ 5.0 uM
S366-0100-B-1	Beta <sub>(x)</sub> 75 @ 10.0 uM
S366-0200-B-1	Beta <sub>(x)</sub> 75 @ 20.0 uM

## Performance Data

Flow direction: Outside-Inside  
 Recommended Changeout: 25 PSID  
 Collapse: 100 PSID  
 Temperature, max: 250 °F  
 Temperature, min: -20 °F

## Material of Construction

Media: Pleated Synthetic  
 Hardware: Plated Steel  
 Bond material: Epoxy

## Packaging

Quantity per carton: 6  
 Weight per carton: 60 lbs