

16433 Foltz Pkwy Strongsville, Ohio 44149 Telephone: (440) 572-1500 Fax: (440) 572-0900  
www.clark-reliance.com



**V264 – 0250 – B – 1**

Element Type/Dimensions

Center Core Material

Absolute Micron Rating

Gasket Material

**Filtration Efficiency Rating: ISO 16889**

<u>Element Part Number</u>	<u>Filtration Efficiency</u>
V264-0010-B-1	Beta <sub>(x)</sub> 200 @ 1.0 uM
V264-0030-B-1	Beta <sub>(x)</sub> 200 @ 3.0 uM
V264-0060-B-1	Beta <sub>(x)</sub> 200 @ 6.0 uM
V264-0120-B-1	Beta <sub>(x)</sub> 200 @ 12.0 uM
V264-0250-B-1	Beta <sub>(x)</sub> 200 @ 25.0 uM

**Performance Data**

Flow direction: Outside-Inside  
 Recommended Changeout: 25 PSID  
 Collapse: 150 PSID  
 Temperature, max: 250 °F  
 Temperature, min: -20 °F

**Material of Construction**

Media: Pleated Microglass  
 Hardware: Plated Steel  
 Bond material: Epoxy

**Packaging**

Quantity per carton: 1  
 Weight: 5 lbs