

A Breakthrough in Resin Bonded Cartridge Design

Resin-Sure cartridges have a unique, proprietary two-stage filtration design to maximize particle removal and service life in viscous fluid filtration applications. An outer, spiral, prefilter wrap increases cartridge strength and eliminates residual debris associated with conventional, machined, resin bonded cartridges.

Resin-Sure filter cartridges are available in eight differentiated removal ratings from 2µm, 5µm, 10µm, 25µm, 50µm, 75µm, 125µm and 150µm pore sizes to meet a wide range of performance requirements.

Applications

- Paints
- Printing Inks
- Adhesives
- Resins
- Emulsions
- Chemical Coatings
- Organic Solvents
- Petroleum Products
- Process Water
- Oilfield Fluids
- Animal Oils
- Waxes
- Plasticizers



Features and Benefits

- Outer, spiral wrap collects large particles and agglomerates, while inner layers control particle removal at rated size.
- Outer wrap increases surface area and eliminates loose debris and contamination caused by machined products.
- Extra-long acrylic fibers provide added strength, resist breakage and migration common with competitive “short fiber” cartridges.
- Available with optimal single-open-end seals (222 o-ring with flat cap) in ABS or nylon.
- Phenolic resin impregnation strengthens cartridge for use with fluid viscosities up to 15,000 SSU (3200 cks).
- Withstands pressure surges up to 150 psid across cartridge (depending on fluid temperature).
- One-piece construction eliminates bypass concerns with multilength cartridges and eases change out.
- Silicone-free construction ensures no contamination to adversely affect adhesion properties of coatings.



WARNING! FAILURE OR IMPROPER SELECTION OR IMPROPER USE OF THE PRODUCTS AND/OR SYSTEMS DESCRIBED HEREIN OR RELATED ITEMS CAN CAUSE DEATH, PERSONAL INJURY AND PROPERTY DAMAGE.
This document and other information from Clark-Reliance Corporation, its subsidiaries and authorized distributors provide product and/or system options for further investigation by users having technical expertise. It is important that you analyze all aspects of your application and review the information concerning the product or system in the current product catalog. Due to the variety of operating conditions and applications for these products or systems, the user, through its own analysis and testing, is solely responsible for making the final selection for the products and systems and assuring that all performance, safety and warning requirements of the application are met.

Resin-Sure Depth Series

Specifications

Materials of Construction:

- Acrylic, long staple fiber; phenolic bonding resin

Type of Construction:

- Coreless, one-piece, rigid resin bonded fibrous matrix

Particle Removal Ratings:

- 2µm, 5µm, 10µm, 25µm, 50µm, 75µm, 125µm and 150µm

Dimensions:

- Outside Diameter: 2-9/16 in (65)
- Inside Diameter: 1-1/8 in (28.6)
- Lengths: Nominal, 10, 20, 30 and 40 in lengths

End Adapters:

- None on double open end style
- ABS (Acrylonitrile Butadiene Styrene) for most applications.
- Nylon (NTC) for aromatic solvents.

Maximum Recommended

Operating Conditions:

- Flow Rate: 10 gpm per 10 in length (38 lpm per 254 mm length)
- Temperature: 250°F (121°C)
- Change Out ΔP: 50 psi (3.5 bar)
- Cartridge Pressure Resistance: 150 psid (10 bar) @ 70°F (21°C)
125 psid (8.6 bar) @ 100°F (38°C)
90 psid (6.2 bar) @ 150°F (65°C)
65 psid (4.5 bar) @ 180°F (82°C)
25 psid (1.7 bar) @ 250°F (121°C)

Environmental/Chemical Compatibility:

- Classified as a nonhazardous material
- Incinerable (8000 BTU/lb)
- Crushable and shredable
- Certified silicone-free
- Suitable for weak acids and bases (pH 5-9)
- Unsuitable for oxidizing agents
- Not recommended for FDA applications

Resin-Sure Length Factors

| Length (in) | Length Factor |
|-------------|---------------|
| 9 | 1.0 |
| 10 | 1.0 |
| 19 | 2.0 |
| 20 | 2.0 |
| 29 | 3.0 |
| 30 | 3.0 |
| 39 | 4.0 |
| 40 | 4.0 |

Resin-Sure Flow Factors (psid/gpm @ 1cks)

| Rating (µm) | Flow Factor |
|-------------|-------------|
| 2 | 0.08 |
| 5 | 0.04 |
| 10 | 0.02 |
| 25 | 0.012 |
| 50 | 0.01 |
| 75 | 0.006 |
| 125 | 0.0013 |
| 150 | 0.0010 |

Flow Rate and Pressure Drop Formulae:

$$\text{Flow Rate (gpm)} = \frac{\text{Clean } \Delta P \times \text{Length Factor}}{\text{Viscosity} \times \text{Flow Factor}}$$

$$\text{Clean } \Delta P = \frac{\text{Flow Rate} \times \text{Viscosity} \times \text{Flow Factor}}{\text{Length Factor}}$$

Notes:

- Clean ΔP** is PSI differential at start.
- Viscosity** is centistokes. Use Conversion Tables for other units.
- Flow Factor** is ΔP/GPM at 1 cks for 10 in (or single).
- Length Factors** convert flow or ΔP from 10 in (single length) to required cartridge length.

Ordering Information

| RSBD | 5 | 29 | TC | N |
|-----------------------------|---------------|------------------|---|---------------------|
| Cartridge Code | Micron Rating | Nominal Length | End Cap Options | Seal Options |
| RSBD = Resin-Sure Cartridge | 2µm | 9 9-3/4" 248mm | Omit = Standard DOE (coreless) | Omit = DOE or XA |
| | 5µm | 10 10" 254mm | C = Tinned Steel Core | N = Buna-N O-Ring |
| | 10µm | 19 19-1/2" 495mm | CXC = Tinned Steel Extended Core | E = EPR O-Ring |
| | 25µm | 20 20" 508mm | OB = Std. Open End/Polypro Spring Closed End | S = Silicone O-Ring |
| | 50µm | 29 29-1/4" 743mm | TC = 222 O-Ring/Flat Cap (ABS Plastic) | V = Viton O-Ring |
| | 75µm | 30 30" 762mm | NTC = Single Open End 222 O-Ring/Flat Cap (Nylon) | |
| | 125µm | 39 39" 961mm | XA = Poly Extender | |
| | 150µm | 39 39" 991mm | XB = Extended Core Open/Polypro Spring Closed End | |
| | 150µm | 40 40" 1016mm | | |